

Operating time

this machine will be prolonged; the machine will serve you more efficiently.

Attentions

- 1. This machine is unavailable for the weakness, unresponsive or psychopathic person (including children), unless under the direction or help from the person who have the responsibility for security. Children should be overseen, so it can be testified that they are not playing with it.
- 2. Before using, put this machine on a stable and even table board; operate according to the above methods.
- 3. Before juicing, first confirm juicing net and rotor clutched in position, and no hard contact between juicing net cutter and transparent cover. Put the transparent cover on, fasten tight the handle, then turn on the machine.
- 4. Before being used, the motor works in running-in phase, there may be slight peculiar smell and spark, this is normal, after the motor works for some period, the above phenomenon will disappear.
- 5. During juicing, make sure there is not too full juice and residue in the middle seat and residue cup, if too full, please cut off power supply, clean up, and then use again.
- 6. During using, do not open the cup cover. In case power supply is on, do not put hand or any ware into the mixing cup or feed port, otherwise, harmful accident may occur or this machine may be damaged.
- 7. In order to prolong service life of this machine, over-temperature protective device is mounted in the motor. If the motor works for a long time or overloaded, when over warning temperature, power supply will automatically cut off. After the

4

Attentions

- motor stops, pull out plug of power supply, wait for the motor to cool (about for 30 min), use again.
- 8. Please make sure to put down the spout before do the extraction,only after the operation,consumers can put up the spout,then it can avoid the rest of source drop down onto the table.
- 9. During operating, please do not leave, never let children operate this machine.
- 10. After operation, do not pour the food out until pull out the plug of power supply.
- 11. Cutters are very sharp, in order to avoid danger, when cleaning a cutter, please put the cutter under water tap for washing, do not wash it with hand.
- 12. This machine must not be used for others beyond regulated purposes.
- 13. In case of damaged power supply cord, in order to avoid danger, replacement must be performed by the manufacturer or its service department or similar professional persons.

Maintenance and cleaning

- 1. This machine shall be often used, so as to keep the motor dry and clean.
- 2. If not using for a long time, please store this machine at a dry and well-ventilated place so as to prevent the motor from being damped and going moldy.
- 3. No washing the main machine. When cleaning, only wipe with wet cloth. Other components may be washed directly with water, such as pushing bar, cover, middle seat, residue cup, juice nozzle cover.

5

Bagotte
JUICE EXTRACTOR
DB-001




Please read all instructions carefully before using

145 mm

315 mm

105克铜版纸, 四色印刷

Diagram of name and position of main components



1

Performances

- 1.For the juicer with large diameter, entire apple or pear can be put in for juicing, no cutting apart needed, easy and quick.
- 2.Design is fine, simple, and beautiful, with combined structure, easy to operate and clean.
- 3.High speed electric motor with overheating protection is adopted, high efficiency, time saving, energy saving, high service life of the motor.
- 4.Safety lock unit for switching is specially designed, in order to make sure safety and reliability in use.
- 5. Design with anti-drip function juice mouth.

Attention before using

- 1.This machine is set with safety unit, when the handle does not fasten the cover or the cutter seat is not fastened, the motor cannot turn, so as to ensure safety for the user.
- 2. When disassembling or assembling the juicer, press the upper of feed port of the cover with your hand, then force the handle to slide in or out of cover slot.
- 3.When disassembling juicing net, first remove the cover and residue barrel, then turn the middle ring up to 30 degrees by holding juicing nozzle with your hand, and take up, the juicing net will automatically leave the rotor.
- 4. In order to avoid damage, before using, first check power supply for compliance with rated voltage.
- 5. Clean all parts able to disassemble (refer to the section of "maintenance and cleaning").
- 6. When assembling, please carefully read the diagram of "name and position of main components".
- 7. Please carefully read the "attentions" before using.

2

Juicing

- 1. Before using, please confirm the button switch of the main machine in stop state, in this way, in case assembly is not completed, starting the main machine can be avoided, so unnecessary damage for persons or property avoided.
- 2. Before juicing, first confirm juicing net and rotor clutched in position, and no hard contact between juicing net cutter and transparent cover. Put the transparent cover on, put the handle into the cover slot, then turn on the machine.
- 3. Before using, please make sure to put the juice mouth to drip position, and after turning off the machine, put the juice mouth to anti-drip position to avoid juice come out without juice cup and make the table dirty.
- 4. For using, assemble according to the diagram of "name and position of main components". Turn on power supply, press switch to let the machine run no-load for 5 sec. Put prepared vegetable or fruit into feed port of the juicer, press with the pushing bar, evenly, hard and slowly, juice of the vegetable or fruit can be found, original, fresh, good for health.
- 5. Note: when pressing food with the pushing bar, force shall be even or indirect, pressing force shall not be more than 1 kg, no too sudden force, otherwise, juicing effect will be reduced.

Operating time

This machine is designed with button switches of O grading, I grading, II grading (O for stop, I for weak grading, II for strong grading). For juicing, select strong grading, for operating time, after operating for 1min, stop for 1min, then use again. After the above operation is performed for three times, stop for 15 min, do not operate until the motor is cooled, in this way, service life of

3